

Specification:

Adapté au PCB 30mm

Max. Puissance de la LED: 38.4w/m

Installation: Surface / Suspendu

Matériaux: Extrudé Aluminium 6063

Finition: Anodisé argenté, noir ou blanc *

Diffuseur: Diffuseur PMMA flexible, peut être un rouleau de 25m (P35)

Longueur : 2000mm or 2500mm en continu **

Taille : Profil (W) 35mm, (H) 68mm

Installation des pilotes: Pilote distant requis

* Couleur de revêtement en poudre personnalisée sur demande. Frais supplémentaires s'appliquent


** Profilé vendu au mètre. Peut être coupé à n'importe quelle longueur jusqu'à 6000 mm

Profilé Aluminium

P35

PU35

PUH35



Diffuseur PMMA

Code: P35-O (Opale, lumière trans. >63%)

Code: P35-N (Nouveau Opale, lumière trans. >74%)

Code: P35-F (Gelée, lumière trans. >89%)

Code: P35-C (Clair, lumière trans. >95%)

Diffuseur NOIR

Code: P35-B (Noir, lumière trans. >22%)

MOQ: 200M

Diffuseur PMMA

Code: PU35-O (Opale, lumière trans. >60%)

Diffuseur PMMA

Code: PUH35-O (Opale, lumière trans. >60%)

Accessoires d'installation:

	Embout en Aluminium (Sans trou) Code: P35-Cap		Kits de suspension Code: Sus.KitsA
	Embout en Aluminium (Sans trou) Code: PU35-Cap		Attaches Murale Code: WN35-WClip
	Embout en Aluminium (Sans trou) Code: PUH35-Cap		Joins 90°A Code: J-90A
	Joins 180°A Code: J-180A		Bouchon en Aluminium CNC (Sans trou) Code: P35-Cap-N
	Dali/Push Conducteur LED Gradable 30/36/60/100W Code: LW-SCD		Attache en métal Code: P35-Clip-M
	Alimentation LED standard IP67 20/30/36/45/60W Code: LW-HLD		Joins 120°A Code: J-120A

